

CMS ECO WALL PANEL

SPECIFICATIONS OF THE CMS ECO WALL PANEL 100mm

Standard Thickness: 100mm \pm 3mm

Installation speed: 15 m² per man-day

Fast installation of the CMS Eco Wall Panel - One panel of 600mm x 3000mm x 100mm is approximately equivalent to 90 pieces of brick

Weight: 138 kg/m²

Total weight of a wall is reduced by approximately 35% due to CMS Eco Wall Panel's hollow core

Fire rating: 2 hours

Compressive strength: 25 N/mm²

Strong - can even be used as a load bearing wall

Other features:

- High quality smooth finishing on both surfaces, ready to receive your favourite finishing, ie. skim coat, paint, wallpaper, tile, etc.
- Interlocking tongue & groove joint to ensure impermeability to water, durability & good fit.
- Can be modified to incorporate water downpipes, M & E utilities, etc.
- Minimal wet works on site – ensuring clean & neat construction job sites.



CMS CONCRETE PRODUCTS

CMS Concrete Products Sdn Bhd (366884-X)

Lot 212 Block 17 KCLD, Jalan Old Airport, 93250 Kuching, Sarawak.

T: 082 - 614 436, 082 - 618 718 F: 082 - 614 406

www.cmsb.com.my/concrete

2011